

Safety Data Sheet dated 27/10/2015, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: PIT STOP magnum

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company:

STAC PLASTIC SPRAY S.R.L. Via E. De Nicola 9/11 10036 Settimo Torinese (To) Italia.

STAC PLASTIC SPRAY S.R.L. Tel. n.. +39 011 8977566 Fax n. +39 011 8977491

Competent person responsible for the safety data sheet:

Montini Vittorino stacplas@stacplastic.com


1.4. Emergency telephone number

STAC PLASTIC SPRAY S.R.L. Tel. n.. +39 011 8977566 Fax n. +39 011 8977491

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

 Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

Safety Data Sheet










PIT STOP magnum

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
42.9 %	GPL	CAS: 68476-40-4 EC: 270-681-9 REACH No.: 01-2119486557-22-XXXX	 2.5/C Compr. Gas H280  2.2/1 Flam. Gas 1 H220 DECLK (CLP)*
6.59 %	ethanediol; ethylene glycol	Index number: 603-027-00-1 CAS: 107-21-1 EC: 203-473-3 REACH No.: 01-2119456816-28	 3.1/4/Oral Acute Tox. 4 H302  3.9/2 STOT RE 2 H373
0.219 %	AMINES,C12-14(EVEN NUMBERED) ALKYLDIMETHYL,N-OXIDES	CAS: 308062-28-4	 3.2/2 Skin Irrit. 2 H315  3.1/4/Oral Acute Tox. 4 H302  4.1/A1 Aquatic Acute 1 H400  4.1/C2 Aquatic Chronic 2 H411  3.3/1 Eye Dam. 1 H318

*DECLK (CLP): This substance is classified in accordance with Note K, Annex VI of EC Regulation CE 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 (Table 3.1) or the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Safety Data Sheet

PIT STOP magnum

Extinguishing media which must not be used for safety reasons:
None in particular.

- 5.2. Special hazards arising from the substance or mixture
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
- 5.3. Advice for firefighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Wash with plenty of water.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
ethanediol; ethylene glycol - CAS: 107-21-1

Safety Data Sheet

PIT STOP magnum

EU - LTE(8h): 52 mg/m³, 20 ppm - STE: 104 mg/m³, 40 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)
 ACGIH - STE: C 100 mg/m³ - Notes: A4 (H) - URT and eye irr

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Spray can	--	--
Odour:	characteristic	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	< -1 ° C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	>1	--	--
Relative density:	1.0 kg/l	--	--
Solubility in water:	100%	--	--
Solubility in oil:		--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	(gas) > 400°C	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

Safety Data Sheet

PIT STOP magnum

9.2. Other information

Properties	Value	Method:	Notes:
kinematic viscosity:	kv > 20,5	--	--
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

GPL - CAS: 68476-40-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 658 mg/l ethanediol; ethylene glycol - CAS: 107-21-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 7712 mg/kg

Test: LD50 - Route: Skin - Species: Mouse > 3500 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 2.5 mg/kg - Duration: 8h ethanediol; ethylene glycol - CAS: 107-21-1

LD50 (RABBIT) ORAL: 5017 MG/KG BW

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- acute toxicity;
- skin corrosion/irritation;
- serious eye damage/irritation;
- respiratory or skin sensitisation;
- germ cell mutagenicity;
- carcinogenicity;
- reproductive toxicity;
- STOT-single exposure;
- STOT-repeated exposure;
- aspiration hazard.

Safety Data Sheet

PIT STOP magnum

SECTION 12: Ecological information

- 12.1. Toxicity
Adopt good working practices, so that the product is not released into the environment.
GPL - CAS: 68476-40-4
a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish Negative 19 mg/l - Duration h: 96
Endpoint: LC50 - Species: Daphnia Negative 14.2 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae Negative 7.7 mg/l - Duration h: 96
ethanediol; ethylene glycol - CAS: 107-21-1
a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish = 72860 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae 6500-13000 mg/l - Duration h: 96
- 12.2. Persistence and degradability
None
N.A.
- 12.3. Bioaccumulative potential
N.A.
- 12.4. Mobility in soil
N.A.
- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

- 14.1. UN number
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
ADR-Class: 2.5°F CAP. 2.2.2.1.6 UN1950
IATA-Class: 2.1
IMDG-Class: 2 Aerosols UN 1950
- 14.4. Packing group
- 14.5. Environmental hazards
Marine pollutant: No
- 14.6. Special precautions for user
IMDG-Page: 2102
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
No

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)

Safety Data Sheet

PIT STOP magnum

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H280 Contains gas under pressure; may explode if heated.

H220 Extremely flammable gas.

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H318 Causes serious eye damage.

This safety data sheet has been completely updated in compliance to Regulation 2015/830.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

Safety Data Sheet

PIT STOP magnum

IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.