

Safety Data Sheet

PIT STOP ROAD RACING KIT

Safety Data Sheet dated 19/4/2017, version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: PIT STOP ROAD RACING KIT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

CAR MAINTENANCE ITEM

Uses advised against:

do not use on humans and animals

1.3. Details of the supplier of the safety data sheet

Company:

STAC PLASTIC SPRAY S.R.L. Via E. De Nicola 9/11 10036 Settimo Torinese (To) Italia.

STAC PLASTIC SPRAY S.R.L. Tel. n.. +39 011 8977566 Fax n. +39 011 8977491

Competent person responsible for the safety data sheet:

Montini Vittorino stacplas@stacplastic.com


1.4. Emergency telephone number

STAC PLASTIC SPRAY S.R.L. Tel. n.. +39 011 8977566 Fax n. +39 011 8977491

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

 Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Safety Data Sheet

PIT STOP ROAD RACING KIT

Other Hazards:

may form explosive vapor / air mixtures in places not well ventilated










SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 40% - < 50%	GPL	CAS: 68476-40-4 EC: 270-681-9 REACH No.: 01-2119486557-22-XXXX	 2.5/C Compr. Gas H280  2.2/1 Flam. Gas 1 H220 DECLK (CLP)*
>= 5% - < 7%	ethanediol; ethylene glycol	Index number: 603-027-00-1 CAS: 107-21-1 EC: 203-473-3 REACH No.: 01-2119456816-28	 3.1/4/Oral Acute Tox. 4 H302  3.9/2 STOT RE 2 H373
>= 0.1% - < 0.25%	AMINES,C12-14(EVEN NUMBERED) ALKYL DIMETHYL,N-OXIDES	CAS: 308062-28-4	 3.2/2 Skin Irrit. 2 H315  3.1/4/Oral Acute Tox. 4 H302  4.1/A1 Aquatic Acute 1 H400  4.1/C2 Aquatic Chronic 2 H411  3.3/1 Eye Dam. 1 H318

*DECLK (CLP): This substance is classified in accordance with Note K, Annex VI of EC Regulation CE 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 (Table 3.1) or the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Frostbite

SECTION 11

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

NONE

Safety Data Sheet

PIT STOP ROAD RACING KIT

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Suitable extinguishing media:
CO2 or Dry chemical fire extinguisher.
 - Extinguishing media which must not be used for safety reasons:
None in particular.
 - 5.2. Special hazards arising from the substance or mixture
 - Do not inhale explosion and combustion gases.
 - Burning produces heavy smoke.
 - 5.3. Advice for firefighters
 - Use suitable breathing apparatus .
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.
-

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment.
 - Remove all sources of ignition.
 - Remove persons to safety.
 - See protective measures under point 7 and 8.
 - 6.2. Environmental precautions
 - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 - Retain contaminated washing water and dispose it.
 - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
 - Suitable material for taking up: absorbing material, organic, sand
 - 6.3. Methods and material for containment and cleaning up
 - Wash with plenty of water.
 - 6.4. Reference to other sections
 - See also section 8 and 13
-

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
 - Avoid contact with skin and eyes, inhalation of vapours and mists.
 - Don't use empty container before they have been cleaned.
 - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 - Contaminated clothing should be changed before entering eating areas.
 - Do not eat or drink while working.
 - See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
 - store in a cool, well ventilated place, away from heat, flames, sparks or other sources of ignition
 - keep only in the original container away from sunlight neighborhoods
 - avoid contact with skin and eyes, inhalation of vapours/mists/dusts.
 - do not use empty containers before they are cleaned.
 - contaminated clothing must be replaced before entering the dining areas.
 - at work do not eat or drink.
 - do not smoke
 - avoid the accumulation of electrostatic charges.
 - Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
 - Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Safety Data Sheet

PIT STOP ROAD RACING KIT

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

inflate and repair tubeless tires

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanediol; ethylene glycol - CAS: 107-21-1

EU - LTE(8h): 52 mg/m³, 20 ppm - STE: 104 mg/m³, 40 ppm - Notes: Bold-type:

Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH - STE: C 100 mg/m³ - Notes: A4 (H) - URT and eye irr

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

Do not expose to temperatures exceeding 50° c.

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Spray can	--	--
Odour:	characteristic	--	--
Odour threshold:	Not Relevant	--	--
pH:	10	--	--
Melting point / freezing point:	<0°C (liquid phase)	--	--
Initial boiling point and boiling range:	>100°C (liquid phase)	--	--
Flash point:	< 0 ° C	--	--
Evaporation rate:	Not Relevant	--	--
Solid/gas flammability:	Not Relevant	--	--
Upper/lower flammability or explosive limits:	Not Relevant	--	--
Vapour pressure:	5,5 bar +/- 1	--	--
Vapour density:	>2	--	--

Safety Data Sheet

PIT STOP ROAD RACING KIT

Relative density:	1.070 kg/l +/- 0.03 (20°C)	--	--
Solubility in water:	complete	--	--
Solubility in oil:	no	--	--
Partition coefficient (n-octanol/water):	Not Relevant	--	--
Auto-ignition temperature:	> 200°C	--	--
Decomposition temperature:	Not Relevant	--	--
Viscosity:	Not Relevant	--	--
Explosive properties:	section 10.3	--	--
Oxidizing properties:	no	--	--

9.2. Other information

Properties	Value	Method:	Notes:
kinematic viscosity:	kv > 2,05 mm ² /s (a 40°C)	--	--
Miscibility:	water	--	--
Fat Solubility:	no	--	--
Conductivity:	Not Relevant	--	--
Substance Groups relevant properties	Not Relevant	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

may form explosive vapor / air mixtures in places not well ventilated

10.4. Conditions to avoid

keep away from heat, sources of ignition
avoid the accumulation of electrostatic charges.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

by thermal decomposition can rid CO_x

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

GPL - CAS: 68476-40-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 658 mg/l ethanediol; ethylene glycol - CAS: 107-21-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 7712 mg/kg

Test: LD50 - Route: Skin - Species: Mouse > 3500 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 2.5 mg/kg - Duration: 8h ethanediol; ethylene glycol - CAS: 107-21-1

Safety Data Sheet

PIT STOP ROAD RACING KIT

LD50 (RABBIT) ORAL: 5017 MG/KG BW

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

GPL - CAS: 68476-40-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish Negative 19 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia Negative 14.2 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae Negative 7.7 mg/l - Duration h: 96

ethanediol; ethylene glycol - CAS: 107-21-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 72860 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae 6500-13000 mg/l - Duration h: 96

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

ADR-UN number: 1950

IATA-Un number: 1950

IMDG-Un number: 1950

14.2. UN proper shipping name

14.3. Transport hazard class(es)

ADR-Class: 2.5°F CAP. 2.2.2.1.6 UN1950

IATA-Class: 2.1

Safety Data Sheet

PIT STOP ROAD RACING KIT

IMDG-Class:	2 Aerosols UN 1950
14.4. Packing group	
14.5. Environmental hazards	
Marine pollutant:	No
14.6. Special precautions for user	
IMDG-Page:	2102
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
No	

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Dir. 98/24/EC (Risks related to chemical agents at work)
 - Dir. 2000/39/EC (Occupational exposure limit values)
 - Regulation (EC) n. 1907/2006 (REACH)
 - Regulation (EC) n. 1272/2008 (CLP)
 - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 - Regulation (EU) 2015/830
 - Regulation (EU) n. 286/2011 (ATP 2 CLP)
 - Regulation (EU) n. 618/2012 (ATP 3 CLP)
 - Regulation (EU) n. 487/2013 (ATP 4 CLP)
 - Regulation (EU) n. 944/2013 (ATP 5 CLP)
 - Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).
1999/13/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1
Product belongs to category: P3a

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H280 Contains gas under pressure; may explode if heated.

H220 Extremely flammable gas.

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H318 Causes serious eye damage.

Paragraphs modified from the previous revision:

SECTION 2: Hazards identification

SECTION 7: Handling and storage

SECTION 9: Physical and chemical properties

SECTION 10: Stability and reactivity

Safety Data Sheet

PIT STOP ROAD RACING KIT

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.