Revision: 11.12.2017



Safety data sheet according to (EU) 2015/830

Printing date 11.12.2017

Version number 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WET PROTECT SPRAY
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Only for proper handling. Chain lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

BUCHER_AG_LANGENTHAL MOTOREX-Schmiertechnik Bern-Zürich-Strasse_31__ CH-4901_Langenthal_ Telefon_+41_(0)62_919_75_75

· Only representative in EU:

MOTOREX Deutschland AG, Bismarckstrasse 28, D-69198 Schriesheim

- · Further information obtainable from: msds@motorex.com
- · 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C6-C7, isoalkanes, cyclenes, <5% of n-hexane

Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cycloalkanes, <12:03% aromatics

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Version number 1.1 Printing date 11.12.2017 Revision: 11.12.2017

Trade name: WET PROTECT SPRAY

			(Contd. of page 1)
F	P102	Keep out of reach of children.	, ,
F	P103	Read label before use.	
F	P210	Keep away from heat, hot surfaces, sparks, open flames are sources. No smoking.	nd other ignition
F	P211	Do not spray on an open flame or other ignition source.	
F	P251	Do not pierce or burn, even after use.	
		? Protect from sunlight. Do not expose to temperatures exceeding information:	g 50 °C/122 °F.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 106-97-8	butane	25-50%	
EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	Flam. Gas 1, H220; Press. Gas C, H280		
EC number: 927-241-2 Reg.nr.: 01-2119473851-33	Hydrocarbons, C6-C7, isoalkanes, cyclenes, <5% of n-hexane	10-25%	
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412		
CAS: 74-98-6	propane	5-10%	
EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	Flam. Gas 1, H220; Press. Gas C, H280		
CAS: 75-28-5	isobutane	1-2.5%	
EINECS: 200-857-2 Index number: 601-004-01-8 Reg.nr.: 01-2119485395-27	Flam. Gas 1, H220; Flam. Liq. 1, H224; Press. Gas C, H280		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

Printing date 11.12.2017 Version number 1.1 Revision: 11.12.2017

Trade name: WET PROTECT SPRAY

(Contd. of page 2)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 4)

Printing date 11.12.2017 Version number 1.1 Revision: 11.12.2017

Trade name: WET PROTECT SPRAY

		(Contd. of page 3)
·DNELs		
Hydrocar	bons, C6-C7, isoalkanes, cyclenes, <	5% of n-hexane
Oral	DNEL/general population/Systemic effects/Long-term	125 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	208 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	125 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-term	871 mg/m3 (worker)
	DNEL/general population/Systemic effects/Long-term	185 mg/m3 (consumer)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Protective gloves to EN374, resistant to oil in use. Standard EN 374 Level 3 control G1 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 1).

- Eve protection: Not required.
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

Fluid

Colour:

yellow fluorescent

· Odour:

Mild

(Contd. on page 5)

Printing date 11.12.2017 Version number 1.1 Revision: 11.12.2017

Trade name: WET PROTECT SPRAY

	(Contd. of page
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : Not applicable, as aerosol.
Flash point:	<-10 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	365 °C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits: Lower: Upper:	1.5 Vol % 8.5 Vol %
Vapour pressure at 20 °C:	2,100 hPa
Density at 20 °C: Relative density Vapour density Evaporation rate	0.711 g/cm³ (ASTM D 4052) Not determined. Not determined. Not applicable.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic: VOC (EC)	Not determined. < 3 mm²/s @ 40 °C (DIN 51562-1) 50.00 %
Solids content: 9.2 Other information	0.0 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Revision: 11.12.2017

Safety data sheet according to (EU) 2015/830

Printing date 11.12.2017

Version number 1.1

Trade name: WET PROTECT SPRAY

(Contd. of page 5) · LD/LC50 values relevant for classification: 106-97-8 butane Inhalative LC50 / 15 min | 1,442.738-1.443 mg/l (rat) LC50 / 15 min 800,000 ppm (rat) LC50 / 2h 1,237 mg/l (mouse) LC50 / 2h 520,400-539,600 ppm (mouse) LC50 / 4h 658 mg/l (rat) NOAEC 4,000-16,000 ppm (rat) NOAEC 7.2-21.4 mg/l (rat) LOAEC 21.6 mg/l (rat) LOAEC 12,000 ppm (rat) Hydrocarbons, C6-C7, isoalkanes, cyclenes, <5% of n-hexane Oral LD50 5,000-15,000 mg/kg (rat) NOAEL 1,000-5,000 mg/kg/24h (rat) Dermal LD50 2,000 mg/kg (rat) 3,160-5,000 mg/kg (rabbit) Inhalative LC50 / 4h 4.951-9.3 mg/l (rat) LC50 / 8h 41-4,467 ppm (rat) LC50 / 8h 5 mg/l (rat) NOAEL 200 ppm (rat) NOAEC 275-10,400 mg/m3 (rat) 74-98-6 propane Inhalative LC50 / 15 min 1,442.738-1.443 mg/l (rat) LC50 / 15 min 800,000 ppm (rat) LC50 / 2h 1,237 mg/l (mouse) 520,400-539,600 ppm (mouse) LC50 / 2h NOAEC 4,000-16,000 ppm (rat) NOAEC 7.214-21.394 mg/l (rat) LOAEC 21.64 mg/l (rat) LOAEC 12,000 ppm (rat) 75-28-5 isobutane Inhalative LC50 / 15 min 1,442.738-1.443 mg/l (rat) LC50 / 15 min 800,000 ppm (rat) LC50 / 2h 1,237 mg/l (mouse) LC50 / 2h 520,400-539,600 ppm (mouse) NOAEC 4,000-16,000 ppm (rat) 7.214-21.394 mg/l (rat) NOAEC LOAEC 21.641 mg/l (rat) 12,000 ppm (rat) LOAEC

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 11.12.2017 Version number 1.1 Revision: 11.12.2017

Trade name: WET PROTECT SPRAY

(Contd. of page 6)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

12.1 To	kicity
Aquatic	toxicity:
106-97-8	B butane
LC50	24.1-147.5 mg/l/96h (fish)
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)
Hydroca	arbons, C6-C7, isoalkanes, cyclenes, <5% of n-hexane
LL50	10-30 mg/l/96h (fish)
LL50	10-30 mg/l/72h (fish)
LL50	100 mg/l/48h (fish)
LL50	100 mg/l/24h (fish)
LLO	10 mg/l/96h (aquatic invertebrates)
	1 mg/l/96h (fish)
EL50	22-46 mg/l/48h (aquatic invertebrates)
	1,000 mg/l/48h (algae / cyanobacteria)
EL50	100 mg/l/24h (aquatic invertebrates)
	1,000 mg/l/24h (algae / cyanobacteria)
EL50	1,000 mg/l/72h (algae / cyanobacteria)
ELO	10 mg/l/48h (aquatic invertebrates)
VOELR	0.182 mg/l/28d (fish)
VOELR	0.317 mg/l/21d (aquatic invertebrates)
NOELR	1,000 mg/l/72h (algae / cyanobacteria)
74-98-6	propane
_C50	24.11-147.54 mg/l/96h (fish)
LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)
75-28-5	isobutane
LC50	24.11-147.54 mg/l/96h (fish)
LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)

· 12.3 Bioaccumulative potential	
106-97-8 butane	
Partition coefficient 1.09-2.8 [] (log Kow) (Bioaccumulation)	
•	(Contd. on page 8)

0)

Version number 1.1 Printing date 11.12.2017 Revision: 11.12.2017

Trade name: WET PROTECT SPRAY

		(Contd. of page 7)		
•	Hydrocarbons, C6-C7, isoalkanes, cyclenes, <5% of n-hexane			
Biodegradability	>80 % (28d) (Biodegradability) (OECD 301 F)			
74-98-6 propane				
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)			
75-28-5 isobutane				
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)			
Biodegradability	100 % (28d) (Biodegradability)			

- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-classification according VwVwS, 17.05.1999): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

· European	waste	catal	logue
------------	-------	-------	-------

gases in pressure containers (including halons) containing hazardous substances

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR/RID/ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR/RID/ADN 1950 AEROSOLS ·IMDG

AEROSOLS

·IATA AEROSOLS, flammable

(Contd. on page 9)

Revision: 11.12.2017

Safety data sheet according to (EU) 2015/830

Printing date 11.12.2017

Version number 1.1

Trade name: WET PROTECT SPRAY

(Contd. of page 8) · 14.3 Transport hazard class(es) · ADR/RID/ADN 2 5F Gases. · Class · Label 2.1 · IMDG, IATA 2.1 · Class 2.1 · Label · 14.4 Packing group · ADR/RID/ADN, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Danger code (Kemler): · EMS Number: F-D.S-U · Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSÓLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR/RID/ADN · Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · Transport category D Tunnel restriction code · IMDG · Limited quantities (LQ) 1L (Contd. on page 10)

Printing date 11.12.2017 Version number 1.1 Revision: 11.12.2017

Trade name: WET PROTECT SPRAY

(Contd. of page 9)

· Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· Relevant phrases

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Abteilung Produktsicherheit

Abbreviations and acronvms:

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 1: Flammable liquids – Category 1 Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.